

Biogenic materials for the decarbonization of the built environment

Francesca Thiébat¹, <https://orcid.org/0000-0003-4478-6693>

Fiamma Morselli¹, <https://orcid.org/0009-0002-3533-699X>

¹ Department of Architecture and Design, Politecnico di Torino, Italia

Primary Contact: Francesca Thiébat, francesca.thiebat@polito.it

This article has been accepted for publication and undergone full peer review but has not been through the copyediting, typesetting, pagination and proofreading process, which may lead to differences between this version and the Version of Record.

Published: Dec 20, 2024
10.36253/techne-16598

Abstract

This contribution highlights the need to reflect on the environmental, cultural, and social value of biogenic construction materials and their role in the roadmap towards climate neutrality. Based on a mapping of European case studies, the essay investigates the diffusion of biogenic materials in architecture, questioning whether their use is limited to experimental cases or if it can be at the base of a decarbonization strategy. The analysis conducted reveals the urgency of adopting technologies and practices that promote the diffusion and scalability of biogenic materials to respond, on the one hand, to energy and environmental regulations and, on the other hand, to contribute effectively and economically sustainably to the demand for net-positive materials, as alternatives to conventional ones.

Keywords: biogenic materials, *whole life carbon*, climate neutrality, prefabrication, sustainable architecture

Please cite this article as: Thiébat, F., Morselli, F. (2024). Biogenic materials for the decarbonization of the built environment. *Techne. Journal of Technology for Architecture and Environment*, Just Accepted.

Towards the decarbonization of the built environment

The European Union, in line with the commitments undertaken in the Paris Agreement, has set itself the goal of achieving climate neutrality by 2050 through the transition to a net-zero greenhouse gas emissions economy. For this purpose, it has developed a 'Long-term strategic vision' and promoted a series of strategic initiatives under the Green Deal.

To align with these objectives, several Member States, have developed specific roadmaps and targets for the decarbonization of their building stock. Italy for Climate published in 2023 the 'Roadmap for Climate Neutrality in Italy', outlining a decarbonization path for the industrial, building, transport and agricultural sectors. In synergy with this initiative, the Green Building Council has published the 'Italian Roadmap for the Decarbonization of Buildings by 2050¹', proposing a systemic approach with 53 objectives distributed in three priority areas: decarbonization of buildings, circularity in the construction sector and quality and resilience of cities.

The final goal is to achieve the 'Net-Zero Whole Life Carbon' building target by 2050 (IEA EBC). This approach goes beyond the emissions associated with the use phase of a building (Operational Carbon, OC), i.e., those associated to the energy needs for heating, cooling, lighting, and domestic hot water production. Whole Life Carbon also considers the equivalent CO₂ emissions² generated by materials during the building's production, construction, use, and end-of-life phases (Embodied Carbon - EC). Furthermore, to achieve net-zero carbon buildings (net-Zero or carbon Neutral³), it considers the benefits and environmental impacts that may emerge beyond the building's life cycle and the quota for compensating for total emissions. Although emissions associated with OC can be mitigated throughout the life cycle, EC is typically characterised by an initial peak, known as a "carbon spike" (Ruta et al., 2024), which is inherently difficult to reduce in subsequent phases. It, therefore, becomes crucial to optimise the choice of materials, construction techniques, and the end-of-life management of buildings.

To initiate a large-scale transition and a consequent significant reduction in carbon emissions, as indicated by the IPCC, a vision for the decarbonization of the built environment seems more appropriate that recognizes the time value of carbon emissions emitted throughout the whole life cycle of the building, that includes compensation strategies in the overall balance (World Green Building Council) and that promotes environmental regeneration and biodiversity (Ichioka & Pawlyn, 2021).

The Global Alliance for Building and Construction, a prominent European body for developing benchmarking methodologies alongside the WGBC, has prioritised the promotion of low-carbon materials to mitigate embodied carbon (EC) throughout the entire building life cycle (Andreotti & Giordano, 2023). This essay will concentrate on biogenic materials within the spectrum of low-carbon options. The term "biogenic" denotes matter derived from biomass (European Committee for Standardization, 2014) either virgin or recycled, encompassing materials such as wood, hemp, straw, mycelium, sheep's wool, shells, algae, and other substances originating from living organisms⁴. A "biogenic product" instead is defined as one that is either wholly or partially derived from biomass. Biogenic materials can be categorised into those sourced from slow-growing resources, such as wood, and "fast-growing materials" (Pomponi et al., 2020; Pittau, 2018; Göswein et al., 2022), such as straw and hemp. Given their shorter crop rotation periods, materials with fast growth cycles have the potential to contribute to decarbonization more effectively (Göswein et al., 2022).

In the architectural context, the application of biogenic-based products for renovation, extension, or new construction frequently includes elements of the building envelope and internal partitions (e.g., plant-fibre insulation or timber cladding) and, in some cases, structural components (e.g., timber or straw bale structural systems). Beyond their intrinsic renewability, biogenic materials play a crucial role in sequestering atmospheric carbon dioxide during their growth phase, as the captured CO₂ is stored as biogenic CO₂ within the built environment (Pittau et al., 2018), thereby transforming the built environment into a carbon sink⁵ (Pomponi et al., 2020; Churkina et al., 2020). The emissions associated with these materials can be mitigated through the cultivation and regeneration of biomass as a new raw material, which, by annually absorbing CO₂ from the atmosphere, contributes to the overall carbon sequestration process (Göswein et al., 2022).

Further characteristics of biogenic building products include non-toxicity, breathability, biodegradability, good thermal properties (Galimshina et al., 2024), the potential for integration into passive systems (Ruta et al., 2024), the capacity to facilitate recovery and reuse processes for agro-food waste (Galimshina et al., 2024) and, finally, the capacity to enhance the social and economic regeneration of local communities (Brunner, 2011; Ruta, 2024; Ichioka & Pawlyn, 2021). Notwithstanding the significant advantages of bio-based building materials in reducing EC, certain limitations persist concerning aesthetics, durability, fire resistance (Jones & Brischke, 2017; Ruta et al., 2024), water resistance, susceptibility to insect and pest infestation, and resource availability (Göswein et al., 2021; Pomponi et al., 2020).

Biogenic Materials: A possible path

The choice of building materials and components in the design phase is intrinsically linked to many considerations, ranging from aesthetic and technological factors to historical-cultural relevance, functionality, and ethical implications. The regulatory and technical constraints must be considered, particularly those related to raw materials availability, durability, and sustainability.

Several authors have argued that replacing high-impact products with low-impact, biogenic ones does not always meet project constraints and required performance. When considering, for example, foundations that must withstand heavy loads and ensure watertightness. Furthermore, other considerations should be made for the limited availability of some low-impact materials in specific geographic areas, where their impact increases due to transportation and their sustainability decreases if the regeneration capacity is exceeded over time (Göswein et al., 2021, 2022; Pomponi et al., 2020). This is the case of wood used in locations where forests do not grow or where the use rate exceeds the growth rate (Pomponi et al., 2020).

Carcassi et al. (2022) draw a comparison between the food pyramid and a "material diet". They argue that to achieve climate neutrality, we must first minimise, where substitution is not possible, the use of materials with a high embodied energy, known as high-carbon materials, such as steel, polymers, and glass; secondly, promote the use of materials with low CO₂ emissions embedded, defined as low-carbon; and finally, prioritise the use of climate-negative construction materials as much as possible due to their ability to absorb and store CO₂. Moreover, as with a food diet, they suggest to diversify products and consider efficiency based on the type of project and location.

Biogenic materials, therefore, represent a fundamental alternative to promote the ecological transition of the built environment. As detailed by Ruta et al. (2024), adopting a 'material diet' during the design phase can enable a 50% reduction in emissions over the entire life cycle when compared

to a conventional building. Furthermore, by considering the use of biogenic materials, particularly fast-growing ones, and the relative contribution of sequestered biogenic CO₂, life cycle emissions reductions can reach 70% (Ruta et al., 2024).

Based on these premises, this essay explores various case studies of contemporary architecture that display the use of biogenic materials. The case studies have been selected within the European geographic context over the last twenty years. This choice is linked to the authors' desire to investigate recently completed projects and to analyse the implementation of biogenic products, components, or materials in Europe.

Tables 01, 02, and 03 present a mapping⁶ of twenty-seven case studies categorised by the type of biogenic material used in an innovative or, in some cases, predominant way. For each architecture, the data presented highlights the project site, year of construction, biogenic technical element, description of the construction system, intended use, whether it is a renovation/extension project or new construction, whether it is public or private, and finally whether the use of the biogenic material is experimental or non-experimental. The main limitations of the case study selection concern the availability of information and technical details (drawings or construction site images). Furthermore, it was necessary to select only a few case studies for materials with a wide availability of examples, such as wood, prioritising those that were particularly significant or pioneering.

TAB: 01, 02 e 03

The case studies were examined to identify the potential and limitations of using biogenic materials at a wide scale to contribute to achieving climate neutrality. The analysis highlighted the need to emphasise some key issues. Firstly, can biogenic materials be used for all technical elements of a building? From the observation of the case studies, only certain materials can be used for the load-bearing structure, in particular wood and straw. Moreover, when wood is excluded, there is often a lack of regulations, and it is up to the individual designer to certify the project. However, two case studies show the possibility of using alternative materials for structural elements, such as cork (CK01) or lime-hemp load-bearing bricks (HP04).

A second theme relates to the construction process. Although the use of biogenic materials is often associated with self-build techniques, especially outside Europe, many projects involve the off-site production of some parts of the building, either as completely prefabricated components or modules (WD02), or as custom-made technical systems to be assembled on site (WD01). It should also be noted that most of the projects analysed are predominantly private buildings with residential use (15 out of 27). This may be due to several factors, including the fact that biogenic products are often inadequately represented in regulations, are still experimental or have limited presence on the market, and are therefore used for small buildings, one or two stories above ground, sometimes owned by the designers themselves. The mapping in some cases shows a discrepancy between the geographic location of the construction site and the origin of the raw materials, as in the case of cork used in buildings in northern Europe (CK01). In other instances, however, the utilisation of biogenic products already available in the local market initiates processes that reinforce existing supply chains by facilitating the transfer of technology across various economic sectors (e.g. agriculture and construction) and promoting reuse strategies aligned with circular economy principles. For example,

straw, a material readily accessible in agricultural and livestock markets, is employed in case studies from France (SW01, SW02) and Switzerland (SW03, SW04).

When examining the construction year of the projects, a significant increase in the use of biogenic materials can be observed. Less than 20% of the analysed projects were constructed between 2000 and 2015, while more than 50% were realised in the last six years. This increase can be considered a positive result attributable to decarbonization strategies implemented at the international level, particularly by the EU in the last decade, and through initiatives directly impacting citizens, such as the New European Bauhaus. Finally, it is important to highlight the experimental nature of the use of biogenic materials in almost 75% of the analysed projects. This theme is further evident in the absence of information regarding supply and installation costs. Specifically, some projects involve educational prototypes used to test materials, as seen in the case of mycelium pavilions (MM01, MM02) others, on the other hand, take up traditional uses in a contemporary key with engineered and certifiable systems, such as reed fibre used in prefabricated panels (RD01); while others still experiment with new forms or processing techniques, such as assemblable blocks (MT04) or biocomposites in additive manufacturing (HK01).

While assessing technical feasibility and scalability it is fundamental for any innovative system, for biogenic materials, it is essential to ensure the replicability of design and construction solutions to avoid isolating them as individual case study. Replicability also means the availability of raw materials. While an increase in the demand and development of new biogenic product supply chains is desirable, it is essential to consider, on the one hand, the existing ecosystems and socio-economic realities (Ichioka & Pawlyn, 2021) and, on the other hand, the utilisation rate of raw materials, which must not exceed the regeneration rate.

The adoption of biogenic materials could be further explored by examining user perceptions, as these materials are often associated with negative connotations. They are often conceived as poor, non-durable, and unfamiliar materials, even though spontaneous architecture and vernacular buildings constitute 'historical prototypes' still very present in Europe. Economic value also influences consumer perception. Generally, a relatively low raw material cost translates to a higher market price in comparison to conventional products due to the lack of a market for biogenic products in the construction industry. Furthermore, they are rarely included in incentives and tax bonus mechanisms, mainly due to a lack of know-how, low industrial scale-up, and the reasons for availability previously highlighted.

As demonstrated by some of the case studies analysed, the prefabrication of biogenic products could enhance production efficiency and construction time, reduce waste, and optimise resource utilisation. This approach would allow for greater quality control, ensuring consistent performance and facilitating product certification and dissemination on the market of biogenic products.

What are the future outlooks for sustainable architecture?

The analysis of European case studies has emphasised a growing interest in utilising biogenic construction materials. Such materials offer substantial environmental benefits and can significantly contribute to the decarbonization of the built environment. This represents a promising pathway that is becoming more tangible. Nonetheless, their application is often restricted to pilot projects that prove challenging to scale-up and replicate due to the absence of specific regulations, limited availability of certified materials, and requisite of technical expertise. Within this context, could

prefabrication be a strategic approach to facilitate the widespread adoption of biogenic materials to a standard practice rather than an isolated instance?

The prefabrication of systems that use fast-growing renewable and circular materials presents an alternative paradigm to conventional construction within a climate-neutral built environment. Aligned with the concept of a 'material diet', there is a pressing need to develop and disseminate knowledge-based 'recipes' composed of interchangeable local resources and raw materials. Such an approach would facilitate the development of 'open systems' that are both adaptable and scalable, thereby promoting resource diversification and fostering a close connection with local ecological systems.

The carbon neutral or net-zero objective represents an initial step towards sustainability but is insufficient to achieve more ambitious goals. Progression towards a 'net-positive' model, which extends beyond mere emissions reduction, is necessary. The carbon-neutral approach, or as Eisenstein (2016) terms it, "CO₂ reductionism⁷", is primarily concerned with mitigating emissions yet frequently overlooks the broader socio-economic and ecological systems. The net-positive approach also seeks to establish net-positive ecological and social value by restoring the environment. The next phase involves transitioning to a regenerative economy, as Jain (2022) defines, characterised by structures that foster resilience, diversity, and interconnectedness of all systems.

This requires businesses, governments, and policymakers to adopt practices that foster regeneration and the configuration of a network of interconnected systems (Fullerton, 2015). Within the architectural context, the transition towards a regenerative model entails transcending the mere minimization of operational and embodied carbon (Ichioka & Pawlyn, 2021) to promote co-evolutionary thinking⁸ (Wahl, 2016; Mang & Haggard, 2016), envisioning a continuous metamorphosis of architecture in relation to its environmental context (Angelucci & Di Sivo, 2019) to design buildings that contribute positively to ecological systems through the utilisation of materials, processes, and systems integrated into natural, social, and cultural cycles. Ichioka and Pawlyn (2011) underline that the regenerative approach in architecture should aspire to global dissemination of knowledge, concurrently incentivising local production. This concept resonates with the principles of Agenda 21, which advocate for 'thinking globally and acting locally'.

Img. 01

Notes

¹ <https://gbcitalia.org/area-download/roadmap/> (last accessed 10/09/2024)

² Equivalent CO₂ is a measure that expresses the impact of greenhouse gases in terms of the amount of carbon dioxide (CO₂) that would have the same global warming potential over a given period of time. It therefore allows the comparison of emissions of different greenhouse gases by converting their emissions into an equivalent amount of CO₂.

³ Foundations-for-net-zero-full-paper.pdf (sciencebasedtargets.org)

⁴ Earth, metals, minerals, and other inert natural materials are excluded from the classification of biogenic materials as they do not originate from living organisms.

⁵ In the architectural context, a carbon sink denotes a building system comprising materials capable of absorbing and storing atmospheric carbon dioxide.

⁶ The selection of case studies (from 1 to 5 for each material), although subjective and not exhaustive, can constitute a first attempt at mapping the current state.

⁷ <https://charleseisenstein.org/essay/grief-and-carbon-reductionism/>

⁸ Co-evolutionary thinking pertains to the concurrent evolution of interacting species.

References

- Angelucci, F., & Di Sivo, M. (2019). Designing for co-evolution. *TECHNE - Journal of Technology for Architecture and Environment*, 120-127. <https://doi.org/10.13128/TECHNE-7518>
- Brunner, P. H. (2011). Urban mining: A contribution to reindustrializing the city. *Journal of Industrial Ecology*, 15, 339–341.
- Carcassi, O. B., Habert, G., Malighetti, L. E., & Pittau, F. (2022). Material diets for climate-neutral construction. *Environmental Science & Technology*, 56(8), 5213–5223. <https://doi.org/10.1021/acs.est.1c05895>
- Carcassi, O. B., Paoletti, I., & Malighetti, L. E. (2021). Reasoned catalogue of biogenic products in Europe: An anticipatory vision between technical potentials and availability. *TECHNE - Journal of Technology for Architecture and Environment*, 63–70. <https://doi.org/10.36253/techne-10578>
- Churkina, G., Organschi, A., Reyer, C. P. O., Ruff, A., Vinke, K., Liu, Z., Reck, B. K., Graedel, T. E., & Schellnhuber, H. J. (2020). Buildings as a global carbon sink. *Nature Sustainability*, 3(4), 269–276. <https://doi.org/10.1038/s41893-019-0462-4>
- Eisenstein, C. (2016). Grief and carbon reductionism. Essay. <https://charleseisenstein.org/essay/grief-and-carbon-reductionism/>
- European Committee for Standardisation. (2016). *EN 16575: Bio-based products – Vocabulary*.
- Fullerton, J. (2015). *Regenerative capitalism: How universal principles and patterns will shape our new economy*. Capital Institute. <http://capitalinstitute.org/wp-content/uploads/2015/04/2015-Regenerative-Capitalism-4-20-15-final.pdf>
- Galimshina, A., Moustapha, M., Hollberg, A., Lasvaux, S., Sudret, B., & Habert, G. (2024). Strategies for robust renovation of residential buildings in Switzerland. *Nature Communications*, 15(1). <https://doi.org/10.1038/s41467-024-46305-9>
- Giordano, R., & Andreotti, J. (2023). Strumenti per la decarbonizzazione: contabilizzazione dell'Embodied Carbon nel ciclo di vita di un manufatto edilizio. *GBC Italia*.
- Göswein, V., Arehart, J., Phan-huy, C., Pomponi, F., & Habert, G. (2022). Barriers and opportunities of fast-growing biobased material use in buildings. *Buildings and Cities*, 3(1), 745–755. <https://doi.org/10.5334/bc.254>
- Göswein, V., Reichmann, J., Habert, G., & Pittau, F. (2021). Land availability in Europe for a radical shift toward bio-based construction. *Sustainable Cities and Society*, 70, 102929. <https://doi.org/10.1016/j.scs.2021.102929>
- Ichioka, S. & Pawlyn, M. (2021). *Flourish: Design paradigms for our planetary emergency*. Triarchy Press.
- IEA EBC. Annex 89 - Ways to implement net-zero whole life carbon buildings.
- Jain, Y. (2021). Regenerative economies: A new approach towards sustainability. In W. Leal Filho, A. M. Azul, L. Brandli, A. Lange Salvia, P. G. Özuyar, & T. Wall (Eds.), *No poverty* (pp. 1–11). Springer International Publishing. https://doi.org/10.1007/978-3-319-69625-6_80-1
- Jones, D., & Brischke, C. (2017). *Performance of bio-based building materials*. Woodhead Publishing.
- Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). *Manual of biogenic house sections*. Oro Editions – Publishers of Architecture, Art, and Design.
- Mang, P. (2016). *Regenerative development and design: A framework for evolving sustainability*.
- Pittau, F., Krause, F., Lumia, G., & Habert, G. (2018). Fast-growing bio-based materials as an opportunity for storing carbon in exterior walls. *Building and Environment*, 129, 117–129.
- Pomponi, F., Hart, J., Arehart, J. H., & D'Amico, B. (2020). Buildings as a global carbon sink? A

reality check on feasibility limits. *One Earth*, 3(2), 157–161.
<https://doi.org/10.1016/j.oneear.2020.07.018>

Ruta, M. F., Pittau, F., & Maserà, G. (2024). Towards zero-carbon buildings: Challenges and opportunities from reversing the material pyramid. *Sustainability*, 16(11), 4454.
<https://doi.org/10.3390/su16114454>

Stern, E., Walther, R., & Rager, M. (2020). *Le tour de France des maisons écologiques*. Alternatives—Grand format—Librairie Gallimard PARIS.

Wahl, D. C. (2016). *Designing regenerative cultures*. Triarchy Press.

Images

Tab 01

Biogenic Material	Project Designers Reference	Location	Year	Biogenic technical elements	Detail	Construction technique	Intended use	Renovation / New construction	Private / Public	Experimental / Non experimental
WOOD FRAME										
Tamedia office Shigeru Ban	WD 01 shigerurbanarchitects.com	Zurich CH	2013			Prefabricated glulam timber elements joined together using traditional Japanese carpentry techniques	Office	●	■	■
Endesa Pavilion IAAC: Arch. Rodrigo Rubio, Miguel Guerrero IAAC - Institute for Advanced Architecture of Catalonia https://iaac.net/	WD 02	Barcelona ES	2011			Modular component wood frame structure	Educational Prototype	●	●	■
Lou Estela Arch. Davide Castellino	WD 03 https://www.daricastellino.it/progetto/abitazione-42-2/	Moiola IT	2021			Prefabricated wood structure - trusses with different sizes to give shape to the ridgeline of the roof	Residential	●	■	■
CENF - Formentera Water Sports Center Arch. Marià Castelló Martínez https://m-ar.net/formentera-water-sports-center/	MT 01	La Savina ES	2019			CLT structure	Sport centre	●	●	■
Mjøstårnet Arch. Voll Arkitekter https://vollark.no/portfolios/mjostarnet/	MT 02	Brumunddal NO	2019			Glulam structure trusses made from light-coloured spruce wood, CLT structure columns	Mixed use, Offices, hotel, public spaces	●	●	■
Delhaize Quai de Rome MDW Architecture + H+G Architects mdw-architecture.com	MT 03	Liège BE	2015			Wood is used throughout the project, from CLT structure to cedar facade cladding	Commercial - Retail Supermarket	●	■	■
House Körts Arch. Zeller & Moye https://www.zeller-moye.com/house-korts/ Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). Manual of Biogenic House sections. Oro Editions.	MT 04	Gross Körts DE	2020			Prefabricated load bearing hollow block and CLT for horizontal structure	Residential	●	■	■
Casa Stella Maris Atelier Werner Schmidt www.werner-schmidt.ch	SW 01	Susch CH	2014			Straw bale external thermal envelope - insulation	Residential	■	■	●
Gartist GmbH House Atelier Werner Schmidt www.werner-schmidt.ch	SW 02	Bubikon CH	2017			Structural jumbo straw bale for both the walls and the roof	Office and showroom	●	■	■

Icon legend Structure Cladding Insulation Partition

Tab 02

Biogenic Material	Project Designers Reference	Location	Year	Biogenic technical elements	Detail	Construction technique	Intended use	Renovation ■ / New construction ♦	Private ■ / Public ♦	Experimental ■ / Non experimental ♦	
STRAW	Bauge Lequertier and Martin Stern, E., Walther, R., & Rager, M. (2020). Le tour de France des maisons écologiques. <i>Alternatives</i> .	SW 03 	Taillebois Orne FR	2018			Self-construction Rammed earth pillars and straw bale infill walls	Residential	♦	■	♦
	Maison Mor Atelier Desmichelle Stern, E., Walther, R., & Rager, M. (2020). Le tour de France des maisons écologiques. <i>Alternatives</i> .	SW 04 	Saint-Nom-La-Bretèche, Yvelines, FR	2015			Structural straw bale and wood frame	Residential	♦	■	♦
	Flat house Practice Architecture Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). Manual of Biogenic House sections. <i>Oro Editions</i> .	HP 01 	Cambridgeshire UK	2019			Modular units built offsite / Prefabricated I-joist wood framed cassettes filled with hemp and lime	Residential	♦	■	■
	Polyvalent Studio Practice Architecture + Unit 7, London Metropolitan University https://practicearchitecture.co.uk/project/cass-studio/	HP 02 	Pidley UK	2019			Prefabricated modules with wood structure, hempcrete walls, wood fibre insulation, hemp fibre bio-resin cladding (Margent Farm)	Atelier	♦	■	■
	Beton de chanvre Daniel Bayol Stern, E., Walther, R., & Rager, M. (2020). Le tour de France des maisons écologiques. <i>Alternatives</i> .	HP 03 	Vidauban Var FR	2015			Wood (douglas fir) structure, insufated hempcrete insulation, earth bricks wall partitions	Residential	♦	■	■
HEMP	Sports hall Lemoal Lemoal Architects Pierre Chevet Sports Hall in Croissy-Beaubourg (theplan.it)	HP 04 	Croissy-Beaubourg FR	2021			Wooden half-vaulted porticos that lean against a structural wall of hempcrete blocks	Sport centre	♦	♦	■
	The voice of urban nature Overtreders W Architectural design Overtreders W I (overtreders-w.nl)	HP 05 	Floriade, Almere NL	2022			Wooden building modules filled with lime hemp and robust constructive columns	Educational Prototype	♦	■	♦
CORK	Cork house Matthew Barnett Howland, Dido Milne, Oliver Wilton https://www.matthewbarnett-howland.com/cork-house	CK 01 	Eton UK	2011			Prefabricated modules of structural cork blocks	Residential	♦	■	■
	Two cork houses Emiliano López Mónica Rivera Arquitectos Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). Manual of Biogenic House sections. <i>Oro Editions</i> .	CK 02 	Palafrugell ES	2016			Structure in CLT panels with cork insulation external skin	Residential	♦	■	♦

Icon legend Structure Cladding Insulation Partition

Tab 03

Biogenic Material	Project Designers Reference	Location	Year	Biogenic technical elements	Detail	Construction technique	Intended use	Renovation ■ / New construction ♦	Private ■ / Public ♦	Experimental ■ / Non experimental ♦
CORK	Casa Quattro LCA Architetti LCA Architetti (Luca Compri Architetti - Varese) - BEN- VENUTI (lcarchitetti.com)	CK 03 	Magnago Milan IT	2016		Wood structure, rice straw infill walls, cork ex- ternal insulating panels	Residential	♦	■	♦
	The day After House Takk the day after house - takk's archive (cargo.site)	CK 04 	Madrid ES	2021		Wood structure and cork panels for insulation and interior clad	Residential	■	■	■
MYCELIUM	Growing pavillion New Heroes Company https://thegrowingpavilion.com	MM 01 	Eindhoven NL	2019		Wood structure, mycelium clad- ding external panels, Bio-textile cot- ton fiber, reed floor	Educational Prototype	♦	♦	■
	MY-CO Space MY-CO X Collective https://www.tu.berlin/en/ub/about-us/contact/public-relations/my-co-space/	MM 02 	Berlin DE	2021		Wood structure, mycelium clad- ding external panels	Educational Prototype	♦	♦	■
HUSK	GAIA. Rice house Rice house Gaia (ricehouse.it)	HK 01 	Massa IT	2018		3D printed walls of earth, straw and ground sand, with rice husk infill	Residential	♦	■	■
	Roseaux Atelier CAZ'eco Stern, E., Walther, R., & Rager, M. (2020). Le tour de France des maisons écologiques. <i>Alternatives</i> .	RD 01 	Savenay, Loire- Atlantique FR	2018		Prefabricated modus with wood frame and reed fiber insulation, reed thatching exter- nal cladding	Residential	♦	■	♦
REED	Dune House Archispektras Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). Manual of Biogenic House sections. <i>Oro Editions</i> .	RD 02 	Pape LV	2016		Modular component wood frame structure	Residential	♦	■	♦
	SkinOver Reed IBBTE University of Stuttgart IBBTE Universität Stuttgart (uni-stuttgart.de)	RD 03 	Brand Bei Bludenz AT	2019		Wood struc- ture (portals) and external insulating and cladding thatched reed	Accommodation	♦	■	■
SEAWEED	Seaweed House Vandkunsten Architects Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). Manual of Biogenic House sections. <i>Oro Editions</i> .	SD 01 	Laesø Island DK	2013		Concrete pier foundations, wood structure, seagrass ex- ternal cladding and insulation	Residential	♦	■	■

Icon legend Structure Cladding Insulation Partition

Captions

Tab. 01 - Case studies divided by type of biogenic material - Source: article authors.

Tab. 02 - Case studies divided by type of biogenic material - Source: article authors.

Tab. 03 - Case studies divided by type of biogenic material - Source: article authors.

Img. 01 – From an efficient to a regenerative model - Source: image re-elaboration from the lecture ‘Building to heal: Building materials as an opportunity for regeneration’ by Prof. Dr. Guillaume Habert and S. & Pawlyn, M. (2021).

Attribution, Acknowledgments, Copyright Rights

Both authors contributed equally to the conceptualisation and writing of this paper.

This publication is part of the project PNRR-NGEU which has received funding from the MUR – DM 118/2023



Finanziato
dall'Unione europea
NextGenerationEU



Ministero
dell'Università
e della Ricerca



Just Accepted

Materiali biogenici per la decarbonizzazione dell'ambiente costruito

Francesca Thiébat¹, <https://orcid.org/0000-0003-4478-6693>

Fiamma Morselli¹, <https://orcid.org/0009-0002-3533-699X>

¹ Dipartimento di Architettura e Design, Politecnico di Torino, Italia

Primary Contact: Francesca Thiébat, francesca.thiebat@polito.it

Abstract

Il contributo richiama la necessità di riflettere sul valore ambientale, culturale e sociale dei materiali da costruzione di origine biogenica e sul ruolo che rivestono all'interno della roadmap verso la neutralità climatica. Partendo da una mappatura di casi studio europei, il saggio si interroga sulla diffusione di tali materiali, chiedendosi se il loro uso sia limitato a casi sperimentali o se possa essere alla base di una strategia di decarbonizzazione.

Dall'analisi emerge l'urgenza di adottare strategie che attivino la diffusione e la scalabilità d'uso dei materiali biogenici per rispondere alle normative energetico-ambientali e per contribuire in modo efficace ed economicamente sostenibile alla domanda di materiali net-positive, alternativi a quelli d'uso ordinario.

Parole chiave: materiali biogenici, whole life carbon, neutralità climatica, prefabbricazione, architettura sostenibile.

Verso la decarbonizzazione dell'ambiente costruito

L'Unione Europea, in linea con gli impegni assunti nell'Accordo di Parigi, si è posta l'obiettivo di raggiungere la neutralità climatica entro il 2050 attraverso la transizione verso un'economia a zero emissioni nette di gas serra. A tal fine, ha elaborato una 'Visione strategica a lungo termine' e ha promosso una serie di iniziative strategiche nell'ambito del Green Deal.

Per allinearsi a questi obiettivi, diversi Stati membri hanno sviluppato roadmap e target specifici per la decarbonizzazione del proprio patrimonio edilizio. *Italy for Climate* ha pubblicato nel 2023 la 'Roadmap per la neutralità climatica dell'Italia', delineando un percorso di decarbonizzazione per i settori industriale, edilizio, dei trasporti e agricolo. In sinergia con tale iniziativa, il Green Building Council ha pubblicato la 'Roadmap Italiana per la decarbonizzazione degli edifici al 2050'¹, proponendo un approccio sistematico con 53 obiettivi distribuiti in tre aree prioritarie:

decarbonizzazione degli edifici, circolarità nel settore delle costruzioni e qualità e resilienza delle città.

L'obiettivo finale è quello di raggiungere il target degli edifici 'Net-Zero Whole Life Carbon' entro il 2050 (IEA EBC). Questo approccio non si limita alle emissioni legate alla fase d'uso di un edificio (*Operational Carbon OC*), ossia quelle dovute al fabbisogno energetico per climatizzazione, illuminazione e produzione di acqua calda sanitaria. La *Whole Life Carbon* considera anche le emissioni di CO₂ equivalente² generate dai materiali durante le fasi di produzione, costruzione, utilizzo e dismissione dell'edificio (*Embodied Carbon EC*). Inoltre, per conseguire edifici a zero emissioni nette di carbonio (*net-zero o carbon neutral*³), tiene conto dei benefici e degli impatti che potrebbero emergere al di là del ciclo di vita dell'edificio, così come della quota per la compensazione delle emissioni complessive. Sebbene l'OC possa essere mitigato lungo tutto il ciclo di vita, l'EC è tipicamente caratterizzato da un picco iniziale, noto come 'carbon spike' (Ruta et al., 2024), difficile da ridurre nelle fasi successive. Diventa quindi cruciale ottimizzare la scelta dei materiali, le tecniche costruttive e la gestione del fine vita degli edifici.

Per avviare una transizione ad ampia scala e una conseguente riduzione significativa delle emissioni di carbonio secondo quanto indicato dall'IPCC, sembra quindi più appropriata una visione per la decarbonizzazione dell'ambiente costruito che riconosca il valore temporale delle emissioni di carbonio emesse nell'intero ciclo di vita dell'edificio, che includa strategie di compensazione nel bilancio complessivo, come suggerisce il World Green Building Council (WGBC) e che promuova la rigenerazione dell'ambiente e la biodiversità (Ichioka e Pawlyn, 2021).

Tra le azioni prioritarie proposte dalla Global Alliance for Building and Construction, principale riferimento europeo per lo sviluppo delle metodologie di riferimento insieme al WGBC, è infatti quella di promuovere l'uso di materiali *low carbon* per ridurre l'EC sull'intero ciclo di vita (Andreotti e Giordano, 2023). Tra i materiali *low carbon*, il saggio si focalizza su quelli di origine biogenica.

Il termine "biogenico" si riferisce a materia derivata da biomassa (European Committee for standardisation, 2014) vergine o riciclata, come ad esempio legno, canapa, paglia, micelio, lana di pecora, conchiglie, alghe e altri materiali che provengono da altri organismi viventi⁴. Il prodotto biogenico si definisce invece come "interamente o parzialmente derivato da biomassa". I materiali biogenici si possono distinguere in materiali derivati da risorse a crescita lenta, come il legno, o a crescita rapida, i "fast-growing materials" (Pomponi et al., 2020; Pittau, 2018; Göswein et al., 2022), come la paglia e la canapa. Questi ultimi possono favorire la decarbonizzazione in modo più efficiente grazie ai brevi periodi di rotazione delle colture (Göswein et al., 2022).

In architettura, l'utilizzo di prodotti a base biogenica per interventi di recupero, ampliamento o nuova costruzione spesso riguarda elementi di involucro e partizioni interne (ad es. isolanti in fibre vegetali o rivestimenti in legno) e talvolta elementi strutturali (ad es. sistemi portanti in legno o in balle di paglia). Oltre a essere rinnovabili in natura, essi svolgono un ruolo cruciale nella cattura dell'anidride carbonica atmosferica durante il loro processo di crescita, in quanto la CO₂ sequestrata viene immagazzinata come CO₂ biogenica all'interno degli edifici (Pittau et al., 2018) creando così un costruito *carbon sink*⁵ (Pomponi et al., 2020; Churkina et al., 2020). Le emissioni associate a questi materiali possono quindi essere compensate dalla piantumazione e ricrescita di biomasse da utilizzare come nuova materia prima che, assorbendo annualmente CO₂ dall'atmosfera, contribuiscono al sequestro complessivo del carbonio (Göswein et al., 2022).

Tra le altre caratteristiche dei prodotti da costruzione biogenici vi sono la non tossicità, la traspirabilità, la biodegradabilità, buone proprietà termiche (Galimshina et al., 2024), la possibilità di integrazione nei sistemi passivi (Ruta et al., 2024), la capacità di attivare processi di recupero e riuso di scarti dal settore agro-alimentare (Galimshina et al., 2024) e, infine, la capacità di incentivare la rigenerazione sociale ed economica di comunità locali (Brunner, 2011; Ruta, 2024; Ichioka and Pawlyn, 2021). Tuttavia, sebbene tali materiali offrano vantaggi significativi per la riduzione della *EC*, permangono alcuni limiti riguardo all'aspetto estetico, alla durabilità, alla resistenza al fuoco (Jones and Brischke, 2017; Ruta et al., 2024), alla resistenza all'acqua, all'attacco di parassiti e alla disponibilità delle risorse (Göswein et al., 2021; Pomponi et al., 2020).

Materiali biogenici: una strada possibile

In fase di progettazione, la scelta di materiali e componenti è fortemente legata a valutazioni estetiche, tecnologiche, storico-culturali, funzionali ed etiche. Allo stesso modo è necessario tenere conto di vincoli normativi e tecnici, inclusa la reperibilità stessa delle materie prime.

Come sostengono diversi autori, la sostituzione di prodotti ad elevato impatto ambientale con prodotti a basso impatto, a base biogenica, non sempre soddisfa i vincoli di progetto e le prestazioni richieste. Si pensi ad esempio alle fondazioni che devono resistere a forti sollecitazioni e garantire la tenuta all'acqua. Oppure alla scarsa disponibilità di alcuni materiali ritenuti a basso impatto ambientale in aree geografiche specifiche il cui impatto aumenta a causa dei trasporti e la cui sostenibilità si abbassa se si supera la capacità di rigenerazione nel tempo (Göswein et al., 2021, 2022; Pomponi et al., 2020). È il caso del legno usato in località in cui non crescono foreste o con un tasso di utilizzo che eccede il tasso di crescita (Pomponi et al., 2020).

Carcassi et al. (2022) paragona la piramide alimentare con la "dieta dei materiali da costruzione". Sostiene che per raggiungere gli obiettivi di neutralità climatica occorra prima di tutto ridurre al minimo, quando non sia possibile la sostituzione, l'utilizzo di materiali con un alto tasso di *Embodied Energy*, definiti *high-carbon*, quali ad esempio acciaio, materiali polimerici e vetro; secondariamente favorire l'utilizzo di materiali caratterizzati da basse emissioni di CO₂, definiti *low-carbon*; e infine preferire il più possibile materiali da costruzione *climate-negative* per la capacità di assorbire e immagazzinare la CO₂. Inoltre, come per la dieta alimentare, suggerisce di diversificare i prodotti e ragionare sull'efficienza in base al tipo di progetto e alla localizzazione.

I materiali biogenici costituiscono quindi una possibile alternativa per favorire la transizione ecologica dell'ambiente costruito soprattutto se adottati su ampia scala. Come approfondito da Ruta et al. (2024), l'adozione in fase di progetto della "dieta dei materiali da costruzione" può consentire una riduzione del 50% delle emissioni lungo l'intero ciclo di vita rispetto a un edificio convenzionale. Inoltre, prendendo in considerazione l'utilizzo di materiali biogenici, in particolare a crescita rapida, e il relativo contributo della CO₂ biogenica sequestrata, la riduzione di emissioni nel ciclo di vita può raggiungere il 70% (Ruta et al., 2024).

Sulla base di queste premesse, il saggio esplora alcuni casi studio di architetture contemporanee realizzate con materiali biogenici. I casi studio sono stati selezionati all'interno del contesto geografico europeo nell'arco temporale degli ultimi vent'anni. Tale scelta è legata alla volontà degli autori di indagare opere recenti e di analizzare la messa in opera di prodotti, componenti o materiali biogenici in Europa.

Le tabelle 01, 02 e 03 riportano una mappatura⁶ di ventisette progetti suddivisi per tipo di materiale biogenico impiegato in forma innovativa o, in alcuni casi, predominante. Per ogni architettura i dati riportati mettono in evidenza il sito di progetto, l'anno di costruzione, gli elementi tecnici realizzati con materiale biogenico, il sistema costruttivo, la destinazione d'uso, se è un progetto di recupero/ampliamento o una nuova costruzione, se è pubblico o privato e infine se l'uso del materiale biogenico è sperimentale o meno. I limiti principali della selezione dei casi studio riguardano la reperibilità delle informazioni e dei dettagli tecnici (disegni o immagini di cantiere). Inoltre, per i materiali con un'ampia disponibilità di esempi, come nel caso del legno, è stato necessario selezionarne solo alcuni privilegiando quelli particolarmente significativi o pionieristici.

TAB: 01, 02, 03

I casi studio sono stati esaminati al fine di identificare potenzialità e limiti nell'uso di materiali biogenici da replicare su larga scala per contribuire al raggiungimento della neutralità climatica. Dall'analisi è emersa la necessità di evidenziare alcuni temi chiave. Innanzitutto, è possibile usare i materiali biogenici per tutti gli elementi tecnici? Dall'osservazione dei casi studio si nota chiaramente che solo alcuni materiali possono essere utilizzati per la struttura portante, in particolare legno e paglia, e, se si esclude il legno, spesso manca la normativa di riferimento e sta al singolo progettista riuscire a certificare il progetto. Tuttavia, due casi studio mostrano la possibilità di utilizzare per le strutture portanti anche materiali alternativi come il sughero (CK01) o la calce-canapa (HP04). Un secondo tema riguarda il processo costruttivo. Nonostante l'uso di materiali biogenici sia spesso associato a tecniche di auto-costruzione, soprattutto al di fuori dell'Europa, molti progetti prevedono la realizzazione di alcune parti del manufatto in officina, sia interi componenti prefabbricati (WD02), sia elementi tecnici realizzati *ad hoc* da assemblare in cantiere (WD01).

Occorre poi mettere in evidenza che la maggior parte dei progetti analizzati sono edifici in prevalenza privati con destinazione d'uso residenziale (15 su 27). Ciò può essere dovuto a diversi fattori, tra cui il fatto che i prodotti a base biogenica spesso sono poco presenti in ambito normativo, sono ancora sperimentali o presentano una limitata diffusione sul mercato e per questo vengono impiegati per edifici di dimensioni ridotte, ad uno o due piani fuori terra, talvolta di proprietà dei progettisti stessi. La mappatura in alcuni casi mostra una discrepanza tra la localizzazione geografica del cantiere e la provenienza delle materie prime, come nel caso del sughero impiegato in edifici nel nord Europa (CK01). In altri casi invece, l'uso di prodotti biogenici già presenti sul mercato locale, innesca processi di crescita delle filiere esistenti attraverso il trasferimento tecnologico tra settori economici diversi (ad es. agricolo / edilizio) e strategie di riuso secondo i principi dell'economia circolare. Un esempio è la paglia impiegata in alcuni casi studio in Francia (SW01, SW02) e in Svizzera (SW03, SW04), materiale già ampiamente presente sul mercato agricolo e zootecnico.

Si può notare inoltre un aumento negli ultimi anni nell'uso di materiali biogenici. Meno del 20% dei progetti analizzati è stato costruito tra il 2000 e il 2015, mentre più del 50% è stato realizzato negli ultimi sei anni. Tale incremento può essere considerato un risultato positivo attribuibile alle strategie per la decarbonizzazione messe in atto nell'ultima decade a livello internazionale e in particolare dall'UE anche attraverso iniziative con ricadute dirette sui cittadini come il New European Bauhaus. È infine importante evidenziare il carattere sperimentale nell'uso dei materiali biogenici in quasi il 75% dei progetti analizzati. Tema che emerge anche dalla mancanza quasi totale di informazioni sui

costi di fornitura e posa. In particolare, alcuni progetti riguardano edifici dimostratori su cui vengono testati i materiali, come nel caso dei padiglioni in micelio (MM01, MM02); altri invece riprendono usi tradizionali in chiave contemporanea con sistemi ingegnerizzati e certificabili, come la fibra di canna palustre utilizzata in pannelli (RD01); mentre altri ancora sperimentano nuove forme o tecniche di lavorazione, come ad esempio blocchi assemblabili (MT04) o biocompositi nella manifattura additiva (HK01).

Mentre la valutazione della fattibilità tecnica e della scalabilità è fondamentale per ogni sistema innovativo, per i materiali biogenici è importante assicurare la replicabilità delle soluzioni progettuali e costruttive, al fine di evitarne l'isolamento a singoli casi studio. Nel caso di materiali biogenici, replicabilità vuol dire anche reperibilità della materia prima. Per quanto sia auspicabile un aumento della domanda e dell'offerta di nuove filiere di prodotti biogenici non si può prescindere dal considerare, da una parte, gli ecosistemi e gli equilibri socio-economici esistenti (Ichioka e Pawlyn, 2021) e, dall'altra, il tasso di utilizzo delle materie prime che non deve superare il tasso di rigenerazione.

Ulteriori indagini sulla diffusione dei materiali biogenici potrebbero essere condotte a partire dalla percezione degli utenti che spesso associano a tali materiali un valore negativo. A volte, infatti, sono percepiti come materiali poveri, poco duraturi e poco conosciuti, nonostante l'architettura spontanea e gli edifici vernacolari costituiscano un 'prototipo storico' ancora molto presente in Europa. Anche il valore economico influenza sulla percezione dei consumatori. In genere, ad un costo della materia prima relativamente basso, corrisponde un prezzo di mercato più alto rispetto a prodotti convenzionali a causa della mancanza di un mercato specifico di prodotti biogenici. Difficilmente poi rientrano in meccanismi di incentivazione, soprattutto per mancanza di know-how, basso scale-up industriale, oltre ai motivi di reperibilità già evidenziati.

Come dimostrano alcuni dei casi studio analizzati, la prefabbricazione di prodotti biogenici potrebbe migliorare l'efficienza nella produzione e nei tempi di costruzione, riducendo gli sprechi e ottimizzando l'uso delle risorse. Questo consentirebbe un maggiore controllo della qualità, garantendo omogeneità nelle prestazioni e favorendo la certificazione e la diffusione sul mercato dei prodotti.

Quali prospettive per un'architettura sostenibile?

L'analisi di casi studio europei, ha sottolineato il crescente interesse per l'utilizzo di materiali da costruzione di origine biogenica. Materiali che, oltre a offrire significativi vantaggi ambientali, possono contribuire in modo significativo alla decarbonizzazione dell'ambiente costruito. Una strada possibile, che sta prendendo forma. Talvolta però la loro applicazione è limitata a progetti pilota difficili da scalare e replicare per la mancanza di normative specifiche, la scarsa disponibilità di materiali certificati e la necessità di competenze tecniche.

In tale ottica, la prefabbricazione può essere una strategia per favorire la diffusione di materiali biogenici come prassi piuttosto che come *unicum*?

La prefabbricazione di sistemi che prevedono l'uso di materiali a crescita rapida e circolari rappresenta un'alternativa alla costruzione convenzionale per un ambiente costruito *climate-neutral*. In linea con il concetto di "dieta dei materiali da costruzione", diventa urgente sviluppare e divulgare il *know-how* con 'ricette' composte da 'ingredienti' locali intercambiabili, ossia risorse e materie prime disponibili sul territorio. Tale approccio permetterebbe di sviluppare 'sistemi aperti' adattabili e

scalabili per promuovere la diversificazione delle risorse e mantenere un legame stretto con i sistemi ecologici locali.

L'obiettivo *carbon neutral* rappresenta un primo passo verso la sostenibilità, ma non è sufficiente. Per raggiungere risultati più ambiziosi, è necessario progredire verso un modello *net-positive* che vada oltre la semplice riduzione delle emissioni. L'approccio *net-zero* o *carbon neutral* o, come definito da Eisenstein (2016) "CO₂ reductionism"⁷, si focalizza sulla riduzione delle emissioni, ma spesso trascura i sistemi sociali, economici ed ecologici più ampi. L'approccio *net-positive*, in aggiunta, mira a creare un valore ecologico e sociale netto positivo, ripristinando e migliorando l'ambiente. Il passo successivo è la transizione verso un'economia rigenerativa, come definita da Jain (2022), costituita da strutture che promuovono la resilienza, la diversità e l'interconnessione dei sistemi.

Questo richiede alle imprese, ai governi e ai politici l'adozione di pratiche che promuovono la rigenerazione e costruzione di una rete di sistemi interconnessi (Fullerton, 2015). In ambito architettonico, la transizione verso un modello rigenerativo implica andare oltre la mera minimizzazione dell'*Operational* e *Embodied Carbon* (Ichioka e Pawlyn, 2021), per promuovere un pensiero co-evolutivo⁸ (Wahl, 2016; Mang e Haggard, 2016), immaginando una metamorfosi continua dell'architettura rispetto al proprio contesto ambientale (Angelucci e Di Sivo, 2019) con edifici che contribuiscono positivamente ai sistemi ecologici attraverso l'uso di materiali, processi e sistemi integrati nei cicli naturali, sociali e culturali. Ichioka e Pawlyn (2021) sottolineano come l'approccio rigenerativo nell'architettura debba mirare a una diffusione globale del sapere, incentivando al contempo la produzione locale. Questo concetto riprende i principi dell'Agenda 21, che invitano a "pensare globalmente, agire localmente"¹.

Fig. 01

Notes

¹ <https://gbcitalia.org/area-download/roadmap/> (accesso 10/09/2024)

² Il CO₂ equivalente è una misura che esprime l'impatto dei gas serra in termini di quantità di anidride carbonica.

³ foundations-for-net-zero-full-paper.pdf (sciencebasedtargets.org) (accesso 10/09/2024)

⁴ Terra, metalli, minerali e altri materiali naturali inerti non sono inclusi nei materiali biogenici poiché non derivano da organismi viventi

⁵ In architettura, *carbon sink* si riferisce a un sistema edilizio caratterizzato da materiali in grado di immagazzinare anidride CO₂.

⁶ La selezione dei casi studio (da 1 a 5 per ciascun materiale) seppur soggettiva e non esaustiva può costituire un primo tentativo di mappatura dello stato attuale.

⁷ <https://charleseisenstein.org/essay/grief-and-carbon-reductionism/> (accesso 10/09/2024)

⁸ Il pensiero co-evolutivo si riferisce all'evoluzione congiunta delle specie che interagiscono tra loro.

References

- Angelucci, F., & Di Sivo, M. (2019). Designing for co-evolution. *TECHNE - Journal of Technology for Architecture and Environment*, 120-127. <https://doi.org/10.13128/TECHNE-7518>
- Brunner, P. H. (2011). Urban mining: A contribution to reindustrializing the city. *Journal of Industrial Ecology*, 15, 339–341.
- Carcassi, O. B., Habert, G., Malighetti, L. E., & Pittau, F. (2022). Material diets for climate-neutral construction. *Environmental Science & Technology*, 56(8), 5213–5223. <https://doi.org/10.1021/acs.est.1c05895>

- Carcassi, O. B., Paoletti, I., & Malighetti, L. E. (2021). Reasoned catalogue of biogenic products in Europe: An anticipatory vision between technical potentials and availability. *TECHNE - Journal of Technology for Architecture and Environment*, 63–70. <https://doi.org/10.36253/techne-10578>
- Churkina, G., Organschi, A., Reyer, C. P. O., Ruff, A., Vinke, K., Liu, Z., Reck, B. K., Graedel, T. E., & Schellnhuber, H. J. (2020). Buildings as a global carbon sink. *Nature Sustainability*, 3(4), 269–276. <https://doi.org/10.1038/s41893-019-0462-4>
- Eisenstein, C. (2016). Grief and carbon reductionism. Essay.
<https://charleseisenstein.org/essay/grief-and-carbon-reductionism/>
- European Committee for Standardisation. (2016). *EN 16575: Bio-based products – Vocabulary*.
- Fullerton, J. (2015). *Regenerative capitalism: How universal principles and patterns will shape our new economy*. Capital Institute. <http://capitalinstitute.org/wp-content/uploads/2015/04/2015-Regenerative-Capitalism-4-20-15-final.pdf>
- Galimshina, A., Moustapha, M., Hollberg, A., Lasvaux, S., Sudret, B., & Habert, G. (2024). Strategies for robust renovation of residential buildings in Switzerland. *Nature Communications*, 15(1). <https://doi.org/10.1038/s41467-024-46305-9>
- Giordano, R., & Andreotti, J. (2023). Strumenti per la decarbonizzazione: contabilizzazione dell'Embodied Carbon nel ciclo di vita di un manufatto edilizio. *GBC Italia*.
- Göswein, V., Arehart, J., Phan-huy, C., Pomponi, F., & Habert, G. (2022). Barriers and opportunities of fast-growing biobased material use in buildings. *Buildings and Cities*, 3(1), 745–755. <https://doi.org/10.5334/bc.254>
- Göswein, V., Reichmann, J., Habert, G., & Pittau, F. (2021). Land availability in Europe for a radical shift toward bio-based construction. *Sustainable Cities and Society*, 70, 102929. <https://doi.org/10.1016/j.scs.2021.102929>
- Ichioka, S. & Pawlyn, M. (2021). *Flourish: Design paradigms for our planetary emergency*. Triarchy Press.
- IEA EBC. *Annex 89 - Ways to implement net-zero whole life carbon buildings*.
- Jain, Y. (2021). Regenerative economies: A new approach towards sustainability. In W. Leal Filho, A. M. Azul, L. Brandli, A. Lange Salvia, P. G. Özuyar, & T. Wall (Eds.), *No poverty* (pp. 1–11). Springer International Publishing. https://doi.org/10.1007/978-3-319-69625-6_80-1
- Jones, D., & Brischke, C. (2017). *Performance of bio-based building materials*. Woodhead Publishing.
- Lewis, P., Tsurumaki, M., & Lewis, D. J. (2022). *Manual of biogenic house sections*. Oro Editions – Publishers of Architecture, Art, and Design.
- Mang, P. (2016). *Regenerative development and design: A framework for evolving sustainability*.
- Pittau, F., Krause, F., Lumia, G., & Habert, G. (2018). Fast-growing bio-based materials as an opportunity for storing carbon in exterior walls. *Building and Environment*, 129, 117–129.
- Pomponi, F., Hart, J., Arehart, J. H., & D'Amico, B. (2020). Buildings as a global carbon sink? A reality check on feasibility limits. *One Earth*, 3(2), 157–161. <https://doi.org/10.1016/j.oneear.2020.07.018>
- Ruta, M. F., Pittau, F., & Masera, G. (2024). Towards zero-carbon buildings: Challenges and opportunities from reversing the material pyramid. *Sustainability*, 16(11), 4454. <https://doi.org/10.3390/su16114454>
- Stern, E., Walther, R., & Rager, M. (2020). *Le tour de France des maisons écologiques*.

Alternatives—Grand format—Librairie Gallimard PARIS.

Wahl, D. C. (2016). *Designing regenerative cultures*. Triarchy Press.

Didascalie

Tab. 01, 02, 03 – Casi studio selezionati per tipo di materiale biogenico - Fonte: autori dell'articolo

Fig. 01 – Da un modello efficiente a uno rigenerativo – Fonte: rielaborazione da “Building to heal: *Building materials as opportunity for regeneration*” lecture del Prof. Dr. Guillaume Habert e da Ichioka, S. & Pawlyn, M. (2021)

Attribuzione, riconoscimenti, diritti d'autore

Entrambi gli autori hanno contribuito in modo paritario alla concettualizzazione e alla scrittura di questo articolo.

Questa pubblicazione è realizzata nell'ambito del progetto PNRR-NGEU finanziato dal MUR tramite DM 117/2023 (o DM 118/2023)"

